| 120 mm -0.013mm   | 49.2 mm <sup>0</sup> -0.05m  | d2 D2       |   |           |
|---|--|-------------|---|-----------|
| 55 mm -0.012mm  |  |             | Chamfer Dimension   | 2 mm      |
|   |  |             | Distance Pressure Point   |           |
|   |  |             | Dynamic Radial Load   | 24975 lbf |
|   |  |             | Static Radial Load  | 22500 lbf |
|   |  |             | Max Speed   | 5000 rpm  |
|   | 1  | 1           | Weight  | 2.82 kg   |
|   | and specifications are provided for<br>reference and evaluation purposes only,<br>and is subject to change without notice.<br>TFL makes no representations, warranties<br>or guarantees as to the appropriateness,<br>accuracy, completeness, or suitability for | Part Number | 3311 DMA, Double Row Angular<br>Contact Ball Bearings (General) |           |
| TFL Bearings Manufacturing Co., Ltd.<br>Building 2, Lushang Phoenix Plaza, 521 Jingde Road, Licheng                   |  | Size        | 55 mm x 120 mm x 49.2 mm  |           |
| District, Jinan City, Shandong Province, China<br>https://sdtflbearing.com<br>info@tflbearing.com<br>0086 15806631151 | any purpose, of the file, information or<br>specifications. You are solely responsible<br>for the use of the file, information or<br>specifications.   | Brand       | TFL   |           |