| 52 mm -0.013mm                                                                                                        | d1 d                                                                                                                                                                                                                       | ∎<br>1:12<br>D1 |                                               |                       |
|-----------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|-----------------------------------------------|-----------------------|
| 25 mm -0.01mm                                                                                                         |                                                                                                                                                                                                                            |                 | Dynamic Radial Load                           | 3218 lbf              |
|                                                                                                                       |                                                                                                                                                                                                                            |                 | Static Radial Load<br>Bore Type               | 900 lbf<br>Taper 1:12 |
|                                                                                                                       |                                                                                                                                                                                                                            |                 | Max Speed                                     | 18000 rpm             |
|                                                                                                                       |                                                                                                                                                                                                                            |                 | Weight                                        | 0.14 kg               |
| TFL BEARING                                                                                                           | This file and any associated information<br>and specifications are provided for<br>reference and evaluation purposes only,                                                                                                 | Part Number     | 1205 EKTN9/C3, Self Aligning Ball<br>Bearings |                       |
| Building 2, Lushang Phoenix Plaza, 521 Jingde Road, Licheng                                                           | and is subject to change without notice.<br>TFL makes no representations, warranties<br>or guarantees as to the appropriateness,<br>accuracy, completeness, or suitability for<br>any purpose, of the file, information or | Size            | 25 mm x 52 mm x 15 mm                         |                       |
| District, Jinan City, Shandong Province, China<br>https://sdtflbearing.com<br>info@tflbearing.com<br>0086 15806631151 | any purpose, of the file, information or<br>specifications. You are solely responsible<br>for the use of the file, information or<br>specifications.                                                                       | Brand           | TFL                                           |                       |