| 72 mm -0.013mm  |  | 1:12<br>D1  |  |            |
|---|--|-------------|--|------------|
| <u>30 mm -0.01mm</u>  |  |             | Dynamic Radial Load                          | 5062 lbf   |
|   |  |             | Static Radial Load                           | 1530 lbf   |
|   |  |             | Bore Type                                    | Taper 1:12 |
|   |  |             | Max Speed                                    | 13000 rpm  |
|   |  |             | Weight                                       | 0.39 kg    |
| <b>TFL BEARING</b>  | This file and any associated information<br>and specifications are provided for<br>reference and evaluation purposes only,   | Part Number | 1306 K/236725,Self Aligning Ball<br>Bearings |            |
| Building 2, Lushang Phoenix Plaza, 521 Jingde Road, Licheng   | and is subject to change without notice.<br>TFL makes no representations, warranties<br>or guarantees as to the appropriateness,<br>accuracy, completeness, or suitability for | Size        | 30 mm x 72 mm x 19 mm                        |            |
| District, Jinan City, Shandong Province, China<br>https://sdtflbearing.com<br>info@tflbearing.com<br>0086 15806631151 | any purpose, of the file, information or<br>specifications. You are solely responsible<br>for the use of the file, information or<br>specifications.                           | Brand       | TFL  |            |