| 180 mm <sup>o</sup> .ozsm<br>d 6 mm <sup>o</sup> .ozm<br>d d d d d d d d d d d d d d d d d d d                        |  |          |   |           |
|---|--|----------|---|-----------|
| 100 mm -0.02mm  |  |          | Dynamic Radial Load                     | 21938 lbf |
|   | Static Radial Load   | 9112 lbf |   |           |
|   | Bore Type  |          |   |           |
|   |  |          | Max Speed                               | 4800 rpm  |
|   |  |          | Weight                                  | 4.8 kg    |
| TFL BEARING   | and specifications are provided for<br>reference and evaluation purposes only,<br>and is subject to change without notice.                           |          | er 2220 KM, Self Aligning Ball Bearings |           |
| TFL Bearings Manufacturing Co., Ltd.<br>Building 2, Lushang Phoenix Plaza, 521 Jingde Road, Licheng                   | TFL makes no representations, warranties<br>or guarantees as to the appropriateness,<br>accuracy, completeness, or suitability for                   | Size     | 100 mm x 180 mm x 46 mm                 |           |
| District, Jinan City, Shandong Province, China<br>https://sdtflbearing.com<br>info@tflbearing.com<br>0086 15806631151 | any purpose, of the file, information or<br>specifications. You are solely responsible<br>for the use of the file, information or<br>specifications. | Brand    | TFL                                     |           |