| 72 mm-0.013mm   | d1 d   | ∃ <u>1:12</u><br>D1 |   |            |
|---|--|---------------------|---|------------|
| 35 mm -0.012mm  |  |                     | Dynamic Radial Load                     | 4275 lbf   |
|   |  |                     | Static Radial Load                      | 1350 lbf   |
|   |  |                     | Bore Type                               | Taper 1:12 |
|   |  |                     | Max Speed                               | 13000 rpm  |
|   |  |                     | Weight                                  | 0.32 kg    |
| TFL BEARING   | and specifications are provided for<br>reference and evaluation purposes only,   | Part Number         | KAM 1207,Self Aligning Ball<br>Bearings |            |
| Building 2, Lushang Phoenix Plaza, 521 Jingde Road, Licheng   | and is subject to change without notice.<br>TFL makes no representations, warranties<br>or guarantees as to the appropriateness,<br>accuracy, completeness, or suitability for<br>any purpose, of the file, information or | Size                | 35 mm x 72 mm x 17 mm                   |            |
| District, Jinan City, Shandong Province, China<br>https://sdtflbearing.com<br>info@tflbearing.com<br>0086 15806631151 | any purpose, of the file, information or<br>specifications. You are solely responsible<br>for the use of the file, information or<br>specifications.   | Brand               | TFL                                     |            |