





| Shoulder Dia Of Inner Ring (d1) | 27.7 mm |
|--------------------------------------|-----------|
| Raceway Diameter Of Outer Ring(E) | 40.2 mm |
| Chamfer Dimension R1,2(min.) | 1 mm |
| Chamfer Dimension R3,4(min.) | 0.6 mm |
| Permissible Axial Displacement(max.) | 1 mm |
| Dynamic Radial Load | 6412 lbf |
| Static Radial Load | 4590 lbf |
| Max Speed | 20000 rpm |
| Weight | 0.12 kg |



TFL Bearings Manufacturing Co., Ltd.

Jinan City, Shandong Province, China https://www.sdtflbearings.com info@sdtflbearing.com +86 15806631151 This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. TFL makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

| 1 | Part Number | N 303 ECP, Single Row Cylindrical Roller Bearings With Inner Ring |
|--------------------|-------------|--|
| , es i, r | Size | 17 mm x 47 mm x 14 mm |
| e | Brand | TFL |