90 mm -0.015mm	$R_{1}$ $R_{1}$ $R_{2}$ $R_{1}$ $R_{2}$ $R_{4}$ $R_{3}$ $R_{1}$ $R_{2}$ $R_{4}$ $R_{3}$ $R_{4}$ $R_{5}$ $R_{4}$ $R_{5}$ $R_{4}$ $R_{5}$ $R_{4}$ $R_{5}$ $R_{5}$			
			Shoulder Dia Of Inner Ring (d1)	68 mm
			Chamfer Dimension R1,2(min.)	1.1 mm
		<u> </u>	Chamfer Dimension R3,4(min.)	1 mm
			Permissible Axial Displacement(max.)	0.5 mm
			Dynamic Radial Load	14738 lbf
			Static Radial Load	15638 lbf
55 mm-0.15mm			Max Speed	8000 rpm
			Weight	0.42 kg
			Shoulder Dia Of Outer Ring (D1)	79.19 mm
		1	Raceway Diameter Of Inner Ring (Fw)	64.5 mm
	This file and any associated information and specifications are provided for reference and evaluation purposes only,	Part Number	NJ 1011 ECP, Single Row Cylindrical Roller Bearings With Inner Ring	
TFL Bearings Manufacturing Co., Ltd.	<ul> <li>and is subject to change without notice.</li> <li>TFL makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for</li> </ul>	Size	55 mm x 90 mm x 18 mm	
Jinan City, Shandong Province, China https://www.sdtflbearing.com info@sdtflbearing.com +86 15806631151	accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.	Brand	TFL	

Г