| 110 mm-0.015mm   | $\begin{array}{c} 22 \text{ mm} \cdot 0.15 \text{mm} \\ R_2 \\ R_1 \\ R_2 \\ R_4 \\ R_3 \\ R_4 \\ R_4 \\ R_4 \\ R_5 \\ R_4 \\ R_5 \\ R_6 \\ R_7 $ |       |   |           |
|--|--|-------|---|-----------|
|  |  |       | Shoulder Dia Of Inner Ring (d1)                                       | 77.5 mm   |
|  |  |       | Chamfer Dimension R1,2(min.)  | 1.5 mm    |
|  |  |       | Chamfer Dimension R3,4(min.)  | 1.5 mm    |
|  |  |       | Permissible Axial Displacement(max.)                                  | 1.4 mm    |
|  |  |       | Dynamic Radial Load   | 24300 lbf |
|  |  |       | Static Radial Load  | 22950 lbf |
| 60 mm 0 45 m   |  |       | Max Speed   | 8000 rpm  |
| 60 mm -0.15mm  |  |       | Weight  | 0.96 kg   |
|  |  |       | Shoulder Dia Of Outer Ring (D1)                                       | 95.1 mm   |
|  |  |       | Raceway Diameter Of Inner Ring (Fw)                                   | 72 mm     |
| TFL BEARING  | This file and any associated information<br>and specifications are provided for<br>reference and evaluation purposes only,   |       | NJ 212 ECM, Single Row Cylindrical<br>Roller Bearings With Inner Ring |           |
| TFL Bearings Manufacturing Co., Ltd.   | <ul> <li>and is subject to change without notice.</li> <li>TFL makes no representations, warranties<br/>or guarantees as to the appropriateness,<br/>accuracy, completeness, or suitability for</li> </ul>   | Size  | 60 mm x 110 mm x 22 mm  |           |
| Jinan City, Shandong Province, China<br>https://www.sdtflbearing.com<br>info@sdtflbearing.com<br>+86 15806631151 | any purpose, of the file, information or<br>specifications. You are solely responsible<br>for the use of the file, information or<br>specifications.   | Brand | TFL   |           |