100 mm-0.015mm	25 mm ^{-0.15mn} R1 R2 R1 R2 R4			
			Shoulder Dia Of Inner Ring (d1)	70.8 mm
			Chamfer Dimension R1,2(min.)	1.5 mm
			Chamfer Dimension R3,4(min.)	1.1 mm
			Permissible Axial Displacement(max.)	1.5 mm
			Dynamic Radial Load	25650 lbf
			Static Radial Load	26550 lbf
55 mm -0.15mm			Max Speed	8000 rpm
			Weight	0.81 kg
			Shoulder Dia Of Outer Ring (D1)	85.7 mm
		r	Raceway Diameter Of Inner Ring (Fw)	66 mm
	This file and any associated information and specifications are provided for reference and evaluation purposes only,		r NJ 2211 ECP, Single Row Cylindrical Roller Bearings With Inner Ring	
TFL Bearings Manufacturing Co., Ltd.	- and is subject to change without notice. TFL makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for	Size	55 mm x 100 mm x 25 mm	
Jinan City, Shandong Province, China https://www.sdtflbearing.com info@sdtflbearing.com +86 15806631151	any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.	Brand	TFL	