




|                           |                         |
|---------------------------|-------------------------|
| Net Weight                | 2.46 kg                 |
| Basic Dynamic Load Rating | 215 kN                  |
| Basic Static Load Rating  | 217 kN                  |
| Reference Speed           | 3900r/min               |
| Breakdown Voltage (DC)    | ≤1000v                  |
| Layer Thickness           | 200 um                  |
| Electrical Resistance     | 50MΩ (Dry); 10MΩ (Damp) |
| Cage Material             | P - Plastic Molded Cage |



TFL Bearings Manufacturing Co., Ltd.

Jinan City, Shandong Province, China  
<https://www.sdtflbearings.com>  
[info@sdtflbearing.com](mailto:info@sdtflbearing.com)  
 +86 15806631151

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. TFL makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

Part Number

Size

Brand

**NUP218-E-TVP2-J20AA-C3**  
**,Current-Insulated Single Row**  
**Cylindrical Roller Bearing**

**90.0 mm x 160.0 mm x 30.0 mm**

**FAG**